NSN 5365-00-556-7389

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-556-7389 **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened Width: Between 0.470 inches and 0.480 inches **Overall Length:** Between 0.780 inches and 0.790 inches **Bore Diameter:** Between 5.750 inches and 5.760 inches Depth: Between 0.240 inches and 0.250 inches **Bore Shape:** Straight **Drive Type:** Externally slotted **Accommodation Type And Quantity:** 4 slots Angle Between Accommodations In Deg: 90.0 **Beveled Thread:** Not included **Setscrew Locking Notch:** Not included Material: Steel, qq-s-634, comp 1045-canceled or steel qq-t-830 comp 1045 Material: Steel comp 1045 or steel qq-t-830 comp 1045 **Material Specification:** Qq-s-634, comp 1045-canceled federal specification 1st material response **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-std-171 finish 3.3.1 military specification single treatment response **Surface Treatment:** Black-oxide mil-std-171 finish 3.3.1 Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5365-00-556-7389

Externally Threaded Ring - Page 2 of 2



Fiig:

T252-d

Mil-std (military Standard):

Mil-std-171 spec.