NSN 5365-00-556-7554

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-556-7554

Thread Pitch Diameters:
+7.8780 to 7.9080 inches
Thread Direction:
Right-hand
Casehardening Indicator:
Not casehardened
Width:
Between 0.470 inches and 0.480 inches
Overall Length:
Between 0.780 inches and 0.790 inches
Thread Size:
7.968-4
Bore Diameter:
Between 6.853 inches and 6.855 inches
Depth:
Between 0.240 inches and 0.250 inches
Bore Shape:
Straight
Screw Thread Series Designator:
Nonstandard
Drive Type:
Slotted face
Material Hardness Rating:
Between 21.0 rockwell c and 27.0 rockwell c
Accommodation Type And Quantity:
4 slots
Angle Between Accommodations In Deg:
90.0
Beveled Thread:
Not included
Bore Annular Internal Serration:
Not included
Setscrew Locking Notch:
Not included
Material:
Steel, aisi 1045 and steel, aisi 1050 and steel, aisi 1137 and steel, aisi 1144
Material:
Steel comp 1045 and steel comp 1050 and steel comp 1137 and steel comp 1144
Surface Treatment:
Oxide
Surface Treatment:
Black oxide

NSN 5365-00-556-7554

Externally Threaded Ring - Page 2 of 2



-			
٠.	hΔ	Iŧ.	ife:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d