## NSN 5365-00-568-5268

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-568-5268 **Thread Class:** За **Thread Pitch Diameters:** +0.8992 to 0.9052 inches **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened Width: Between 0.240 inches and 0.250 inches **Overall Length:** 0.389 inches **End Radius:** 0.685 inches **Thread Size:** 1-5/8 in.-18 thd size **Bore Diameter:** 1.312 inches Depth: Between 0.182 inches and 0.187 inches Bore Shape: Straight **Screw Thread Series Designator:** Unef or nef **Drive Type:** Slotted face **Material Hardness Rating:** C26 to c33 **Thread Location:** Both ends **Accommodation Type And Quantity:** Angle Between Accommodations In Deg: 90.0 **Beveled Thread:** Included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included

Both ends

Accommodation Type And Quantity:
4 slots

Angle Between Accommodations In Deg:
90.0

Beveled Thread:
Included

Bore Annular Internal Serration:
Not included

Setscrew Locking Notch:
Not included

Bore Edge Process:
Rounded

## NSN 5365-00-568-5268

Externally Threaded Ring - Page 2 of 2



Process End Location:
Drive end
Material:
Steel, mil-s-6736, cond a
Surface Treatment:
Oxide
Surface Treatment:
Black oxide
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: T252-d