

View Online at <https://aerobasegroup.com/nsn/5365-00-572-4371>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Casehardening Indicator:**

Not casehardened

**Width:**

0.190 inches

**Overall Length:**

0.510 inches

**Thread Size:**

0.875-14

**Bore Diameter:**

0.560 inches

**Depth:**

0.120 inches

**Bore Shape:**

Straight

**Screw Thread Series Designator:**

Unf

**Drive Type:**

Slotted face

**Thread Location:**

End opposite drive end

**Accommodation Type And Quantity:**

2 slots

**Angle Between Accommodations In Deg:**

180.0

**Beveled Thread:**

Included

**Bore Annular Internal Serration:**

Not included

**Setscrew Locking Notch:**

Included

**Material:**

Steel, qq-s-763

**Material:**

Steel comp 202 or steel comp 302 or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 322 or steel comp 324 or steel comp 347 or steel comp 633 or steel comp 634 or steel comp 403 or steel comp 405 or steel comp 410 or steel comp 414 or steel comp 416 or steel comp 416se or steel comp 420 or steel comp 430 or steel comp 430f or steel comp 430fse or steel comp 431 or steel comp 440a or steel comp 440b or steel comp 440c or steel comp 440f or steel comp 440fse or steel comp 446

**Precious Material:**

Silver

**Surface Treatment:**

**Surface Treatment:**

Silver plated with rhodium flash

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T252-d