NSN 5365-00-579-7494

Thread Pitch Diameters:

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-579-7494

+1.6629 to 1.6660 inches
Thread Direction:
Right-hand
Casehardening Indicator:
Not casehardened
Overall Length:
0.130 inches
Diameter:
0.063 inches
Taper Minor Diameter:
1.320 inches
Taper Major Diameter:
1.530 inches
Thread Size:
1-11/16 in32
Depth:
0.040 inches
Bore Shape:
Tapered
Screw Thread Series Designator:
Na
Ns
Drive Type:
Drive Type:
Drive Type: Drilled face
Drive Type: Drilled face Accommodation Type And Quantity:
Drive Type: Drilled face Accommodation Type And Quantity: 2 holes
Drive Type: Drilled face Accommodation Type And Quantity: 2 holes Angle Between Accommodations In Deg:
Drive Type: Drilled face Accommodation Type And Quantity: 2 holes Angle Between Accommodations In Deg: 180.0
Drive Type: Drilled face Accommodation Type And Quantity: 2 holes Angle Between Accommodations In Deg: 180.0 Radius From Geometric Axis To Accommodation:
Drive Type: Drilled face Accommodation Type And Quantity: 2 holes Angle Between Accommodations In Deg: 180.0 Radius From Geometric Axis To Accommodation: 0.750 inches
Drive Type: Drilled face Accommodation Type And Quantity: 2 holes Angle Between Accommodations In Deg: 180.0 Radius From Geometric Axis To Accommodation: 0.750 inches Beveled Thread:
Drive Type: Drilled face Accommodation Type And Quantity: 2 holes Angle Between Accommodations In Deg: 180.0 Radius From Geometric Axis To Accommodation: 0.750 inches Beveled Thread: Not included
Drive Type: Drilled face Accommodation Type And Quantity: 2 holes Angle Between Accommodations In Deg: 180.0 Radius From Geometric Axis To Accommodation: 0.750 inches Beveled Thread: Not included Taper Major Diameter Location:
Drive Type: Drilled face Accommodation Type And Quantity: 2 holes Angle Between Accommodations In Deg: 180.0 Radius From Geometric Axis To Accommodation: 0.750 inches Beveled Thread: Not included Taper Major Diameter Location: Opposite drive end
Drive Type: Drilled face Accommodation Type And Quantity: 2 holes Angle Between Accommodations In Deg: 180.0 Radius From Geometric Axis To Accommodation: 0.750 inches Beveled Thread: Not included Taper Major Diameter Location: Opposite drive end Bore Annular Internal Serration:
Drive Type: Drilled face Accommodation Type And Quantity: 2 holes Angle Between Accommodations In Deg: 180.0 Radius From Geometric Axis To Accommodation: 0.750 inches Beveled Thread: Not included Taper Major Diameter Location: Opposite drive end Bore Annular Internal Serration: Not included
Drive Type: Drilled face Accommodation Type And Quantity: 2 holes Angle Between Accommodations In Deg: 180.0 Radius From Geometric Axis To Accommodation: 0.750 inches Beveled Thread: Not included Taper Major Diameter Location: Opposite drive end Bore Annular Internal Serration: Not included Setscrew Locking Notch:
Drive Type: Drilled face Accommodation Type And Quantity: 2 holes Angle Between Accommodations In Deg: 180.0 Radius From Geometric Axis To Accommodation: 0.750 inches Beveled Thread: Not included Taper Major Diameter Location: Opposite drive end Bore Annular Internal Serration: Not included Setscrew Locking Notch: Not included

Aluminum alloy 2024

NSN 5365-00-579-7494

Externally Threaded Ring - Page 2 of 2



Surface Treatment:
Paint
Surface Treatment:
Painted
Fsc Application Data:
Sight, infinity m44, fire control
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: T252-d