## NSN 5365-00-582-7006

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-582-7006

Thread Pitch Diameters:
+0.8788 to 0.8814 inches
Thread Direction:
Right-hand
Casehardening Indicator:
Not casehardened
Overall Length:
0.080 inches
Diameter:
0.128 inches
Thread Size:
0.8915 in64
Bore Diameter:
0.562 inches
Depth:
0.080 inches
Bore Shape:
Straight
Screw Thread Series Designator:
Nonstandard
Drive Type:
Drilled face
Material Hardness Rating:
94.000 rockwell b
Thread Location:
Both ends
Accommodation Type And Quantity:
2 holes
Angle Between Accommodations In Deg:
180.0
Radius From Geometric Axis To Accommodation:
0.295 inches
Beveled Thread:
Included
Bore Annular Internal Serration:
Not included
Setscrew Locking Notch:
Not included
Material:
Steel, qq-s-766, class 2, cond a
Material:
Steel comp 302

## NSN 5365-00-582-7006

Externally Threaded Ring - Page 2 of 2



Surface Treatment:
Passivate
Surface Treatment:
Passivated
Fsc Application Data:
Heading display panel, navigational instrument aircraft
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

T252-d