## NSN 5365-00-597-8827

Aluminum alloy, ww-t-789-canceled

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-597-8827 **Thread Class:** 2a **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Overall Length:** 0.313 inches Diameter: 0.094 inches **Taper Minor Diameter:** 1.770 inches **Taper Major Diameter:** Between 1.182 inches and 1.184 inches **Thread Size:** 2-5/16 in.-32 Depth: 0.063 inches **Bore Shape: Tapered Screw Thread Series Designator:** Uns **Drive Type:** Drilled face **Accommodation Type And Quantity:** 2 holes Angle Between Accommodations In Deg: **Radius From Geometric Axis To Accommodation:** 1.030 inches **Beveled Thread:** Not included **Taper Major Diameter Location:** Opposite drive end **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Special Features:** 11 degree 30 min angle for tapered center hole to obtain maximum diameter and 20 degree angle from face of thds to outer edge on drive end Material:

## NSN 5365-00-597-8827

Externally Threaded Ring - Page 2 of 2



	ria	

Aluminum alloy 6061 or aluminum alloy 6062

**Surface Treatment:** 

Black dye

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

T252-d