## NSN 5365-00-597-8884

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-597-8884 **Thread Class:** За **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Chamfer Angle In Deg:** 13.0 **Chamfer Length:** Any acceptable Width: 0.031 inches **Overall Length:** 0.188 inches **End Radius:** Any acceptable **Thread Size:** 0.743 in.-48 **Bore Diameter:** 0.666 inches Depth: 0.031 inches **Bore Shape:** Straight **Screw Thread Series Designator:** Uns **Drive Type:** Slotted face **Material Hardness Rating:** Not rated **Accommodation Type And Quantity:** Angle Between Accommodations In Deg: 180.0 **Beveled Thread:** Not included **Bore Annular Internal Serration:** Included **Setscrew Locking Notch:** Not included **Bore Edge Process:** 

Chamfered

## **NSN 5365-00-597-8884**Externally Threaded Ring - Page 2 of 2

T252-d



| Process End Location:  |
|--|
| End opposite drive end   |
| Material:  |
| Copper alloy, mil-t-46072  |
| Material:  |
| Copper alloy 330 or copper alloy 331 or copper alloy 332 or copper alloy 370 |
| Surface Treatment:   |
| Oxide  |
| Surface Treatment:   |
| Black oxide  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |