NSN 5365-00-601-7675

Oxide

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-601-7675

Thread Pitch Diameters:
+2.8260 to 2.8300 inches
Thread Direction:
Right-hand
Casehardening Indicator:
Not casehardened
Width:
0.400 inches
Overall Length:
0.812 inches
Thread Size:
2.878 in1
Bore Diameter:
2.078 inches
Depth:
0.281 inches
Bore Shape:
Straight
Screw Thread Series Designator:
Non std
Drive Type:
Slotted face
Material Hardness Rating:
C16 to c27
Accommodation Type And Quantity:
4 slots
Angle Between Accommodations In Deg:
90.0
Beveled Thread:
Not included
Bore Annular Internal Serration:
Not included
Setscrew Locking Notch:
Not included
Special Features:
Counterbored on end opposite drive end 0.312 in. Deep by 2.362 in. Dia; externally relieved on end opposite to drive end 0.132 in. Deep by
2.748 in. Od
Material:
Steel, qq-s-634, comp 1045-canceled
Material:
Steel comp 1045
Surface Treatment:

NSN 5365-00-601-7675

Externally Threaded Ring - Page 2 of 2



Surface Treatment:
Black oxide
Fsc Application Data:
Recoil mechanism, m1a7 and m1a8, 75 mm howitzer
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: T252-d