## NSN 5365-00-607-2524

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-607-2524 **Thread Class:** 2a **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Overall Length:** Between 0.843 inches and 0.853 inches Diameter: Between 3.335 inches and 3.345 inches **Thread Size:** 3.500-16 **Bore Diameter:** Between 2.610 inches and 2.615 inches **Bore Shape:** Straight **Screw Thread Series Designator:** Un **Drive Type:** Lug face **Accommodation Type And Quantity:** 8 lugs **Angle Between Accommodations In Deg: Radius From Geometric Axis To Accommodation:** 1.625 inches **Beveled Thread:** Not included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included Height: Between 0.440 inches and 0.445 inches Material: Steel, qq-t-830, comp 1015 to 1025 cond hr Material: Steel, qq-t-830, comp 1015 to 1025 cond hr **Surface Treatment:** 

Phosphate coated, manganese base or zinc base, phosphate coated

Shelf Life: N/a

## NSN 5365-00-607-2524

Externally Threaded Ring - Page 2 of 2



**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

T252-d