NSN 5365-00-615-5406

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-615-5406

Thread Pitch Diameters:
+0.7065 to 0.7097 inches
Thread Direction:
Right-hand
Casehardening Indicator:
Not casehardened
Chamfer Angle In Deg:
45.0
Chamfer Length:
0.020 inches
Width:
0.080 inches
Overall Length:
0.590 inches
Thread Size:
19mm - 1.5mm
Bore Diameter:
0.331 inches
Depth:
0.080 inches
Bore Shape:
Straight
Screw Thread Series Designator:
Iso m
Drive Type:
Slotted face
Material Hardness Rating:
C16 to c27
Accommodation Type And Quantity:
2 slots
Angle Between Accommodations In Deg:
180.0
Beveled Thread:
Not included
Bore Annular Internal Serration:
Not included
Setscrew Locking Notch:
Not included
Bore Edge Process:
Chamfered
Process End Location:
Both ends

NSN 5365-00-615-5406

T252-d

Externally Threaded Ring - Page 2 of 2



Special Features:
63 microinches rms finish on center hole
Material:
Steel, qq-s-637, comp 1117 and steel, qq-s-637, comp 1137
Material:
Steel comp 1117 and steel comp 1137
Surface Treatment:
Oxide
Surface Treatment:
Black oxide
Fsc Application Data:
Recuperator cylinder head, recoil mechanism, carriage, gun, 155mm, m3
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filg: