Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-615-5884

| Thread Pitch Diameters: | |
|---|--|
| +5.2010 to 5.2160 inches | |
| Thread Direction: | |
| Right-hand | |
| Casehardening Indicator: | |
| Not casehardened | |
| Width: | |
| Between 0.400 inches and 0.410 inches | |
| Overall Length: | |
| Between 0.460 inches and 0.470 inches | |
| Thread Size: | |
| 5.281-7 | |
| Bore Diameter: | |
| Between 4.409 inches and 4.413 inches | |
| Depth: | |
| Between 0.200 inches and 0.210 inches | |
| Bore Shape: | |
| Straight | |
| Screw Thread Series Designator: | |
| Nonstandard | |
| Drive Type: | |
| Slotted face | |
| Material Hardness Rating: | |
| Between 16.0 rockwell c and 27.0 rockwell c | |
| Accommodation Type And Quantity: | |
| 4 slots | |
| Angle Between Accommodations In Deg: | |
| 90.0 | |
| Beveled Thread: | |
| Not included | |
| Bore Annular Internal Serration: | |
| Not included | |
| Setscrew Locking Notch: | |
| Not included | |
| Material: | |
| Steel, aisi 1045 | |
| Material: | |
| Steel comp 1045 | |
| Surface Treatment: | |
| Zinc | |
| Surface Treatment: | |
| Zinc plated | |
| | |

NSN 5365-00-615-5884

Externally Threaded Ring - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d

