NSN 5365-00-615-5884

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-615-5884 **Thread Pitch Diameters:** +5.2010 to 5.2160 inches **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened Width: Between 0.400 inches and 0.410 inches **Overall Length:** Between 0.460 inches and 0.470 inches **Thread Size:** 5.281-7 **Bore Diameter:** Between 4.409 inches and 4.413 inches Between 0.200 inches and 0.210 inches **Bore Shape:** Straight **Screw Thread Series Designator:** Nonstandard **Drive Type:** Slotted face **Material Hardness Rating:** Between 16.0 rockwell c and 27.0 rockwell c **Accommodation Type And Quantity:** 4 slots Angle Between Accommodations In Deg: 90.0 **Beveled Thread:** Not included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included Material: Steel, aisi 1045 Material: Steel comp 1045 **Surface Treatment:**

Zinc **Surface Treatment:** Zinc plated

NSN 5365-00-615-5884

Externally Threaded Ring - Page 2 of 2



\sim				
•	no	ıŦ	ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d