NSN 5365-00-617-1003

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-617-1003 **Thread Class:** За **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Overall Length:** 0.990 inches Diameter: 0.391 inches **Thread Size:** 4-1/2 in. -12 **Bore Diameter:** 3.000 inches Depth: 0.313 inches **Bore Shape:** Straight **Screw Thread Series Designator:** Un **Drive Type:** Drilled face **Accommodation Type And Quantity:** 4 holes Angle Between Accommodations In Deg: 90.0 **Radius From Geometric Axis To Accommodation:** 1.875 inches **Beveled Thread:** Not included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Special Features:** 4 holes equally spaced between drive points; (1) no. 10 (0.190 in.)-32nf-2, (2) 1/4in. Deep; 1/16in. Radius on end opposite to drive end Material: Steel, qq-s-634, comp 1018-canceled and steel, qq-s-634, comp 1022-canceled

Surface Treatment:

Steel comp 1018 and steel comp 1022

Phosphate

Material:

NSN 5365-00-617-1003

Externally Threaded Ring - Page 2 of 2



_	•	-			
Sur	tace	Trea	ıtm	en	m:

Phosphate

Fsc Application Data:

Mount, howitzer, 155-mm, m14

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

T252-d