NSN 5365-00-627-4126

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-627-4126

Thread Class:				
2a				
Thread Pitch Diameters:				
+1.4740 to 1.4797 inches				
Thread Direction:				
Right-hand				
Casehardening Indicator:				
Not casehardened				
Width:				
0.040 inches				
Overall Length:				
0.400 inches				
Thread Size:				
1.500-32				
Bore Diameter:				
Between 1.250 inches and 1.252 inches				
Depth:				
0.188 inches				
Bore Shape:				
Straight				
Screw Thread Series Designator:				
Uns				
Drive Type:				
Slotted face				
Thread Location:				
Both ends				
Accommodation Type And Quantity:				
8 slots				
Angle Between Accommodations In Deg:				
45.0				
45.0				
Beveled Thread:				
Beveled Thread:				
Beveled Thread: Included				
Beveled Thread: Included Bore Annular Internal Serration:				
Beveled Thread: Included Bore Annular Internal Serration: Not included				
Beveled Thread: Included Bore Annular Internal Serration: Not included Setscrew Locking Notch:				
Beveled Thread: Included Bore Annular Internal Serration: Not included Setscrew Locking Notch: Not included				
Beveled Thread: Included Bore Annular Internal Serration: Not included Setscrew Locking Notch: Not included Material:				
Beveled Thread: Included Bore Annular Internal Serration: Not included Setscrew Locking Notch: Not included Material: Aluminum alloy ww-t-700/6 temper t6				
Beveled Thread: Included Bore Annular Internal Serration: Not included Setscrew Locking Notch: Not included Material: Aluminum alloy ww-t-700/6 temper t6 Material:				

NSN 5365-00-627-4126

Externally Threaded Ring - Page 2 of 2



	Trea	

Anodize mil-a-8625 type 2 class 1

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d