

View Online at <https://aerobasegroup.com/nsn/5365-00-629-2187>

Thread Pitch Diameters:

+5.0659 to 5.0709 inches

Thread Direction:

Right-hand

Casehardening Indicator:

Not casehardened

Overall Length:

1.187 inches

Diameter:

0.344 inches

Thread Size:

5-1/8 in.-12

Bore Diameter:

2.516 inches

Depth:

0.375 inches

Bore Shape:

Straight

Screw Thread Series Designator:

Nonstandard

Drive Type:

Drilled face

Material Hardness Rating:

C20 to 21

Accommodation Type And Quantity:

3 holes

Angle Between Accommodations In Deg:

120.0

Radius From Geometric Axis To Accommodation:

2.250 inches

Beveled Thread:

Not included

Bore Annular Internal Serration:

Not included

Setscrew Locking Notch:

Not included

Special Features:

12 holes 5/16-24nf-3 by 1/2 in. Deep equally spaced on 4-1/2 in. Bolt circle located on drive end; end opposite to drive end counterbored 0.437 in. Deep by 4.5 in. Dia

Material:

Steel, qq-s-634, comp 1045-canceled and steel, qq-s-637, comp 1137

Material:

Steel comp 1045 and steel comp 1137

Surface Treatment:

Phosphate

Surface Treatment:

Phosphate

Fsc Application Data:

Jack assgmbly, firing carriage, howitzer, 155mm, m1a2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d