## NSN 5365-00-633-3681

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-633-3681 **Thread Pitch Diameters:** +0.8992 to 0.9052 inches **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened Chamfer Angle In Deg: 45.0 **Chamfer Length:** 0.031 inches Width: 0.0625 inches **Overall Length:** 0.250 inches **Thread Size:** 0.906-32 **Bore Diameter:** 0.703 inches Depth: 0.0625 inches Bore Shape: Straight **Screw Thread Series Designator:** Uns **Drive Type:** Slotted face **Material Hardness Rating:** Between 39.0 rockwell c and 47.0 rockwell c **Accommodation Type And Quantity:** 2 slots Angle Between Accommodations In Deg: 180.0 **Beveled Thread:** Not included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included

**Bore Edge Process:** Chamfered **Process End Location:** End opposite drive end

## NSN 5365-00-633-3681

Externally Threaded Ring - Page 2 of 2



Material:
Steel, ams 5643
Material:
Steel comp 630
Surface Treatment:
Passivate
Surface Treatment:
Passivated
Fsc Application Data:
Gyroscope, displacement
<b>Departure From Cited Designator:</b>
Nouf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

T252-d