

View Online at <https://aerobasegroup.com/nsn/5365-00-633-3681>

**Thread Pitch Diameters:**

+0.8992 to 0.9052 inches

**Thread Direction:**

Right-hand

**Casehardening Indicator:**

Not casehardened

**Chamfer Angle In Deg:**

45.0

**Chamfer Length:**

0.031 inches

**Width:**

0.0625 inches

**Overall Length:**

0.250 inches

**Thread Size:**

0.906-32

**Bore Diameter:**

0.703 inches

**Depth:**

0.0625 inches

**Bore Shape:**

Straight

**Screw Thread Series Designator:**

Uns

**Drive Type:**

Slotted face

**Material Hardness Rating:**

Between 39.0 rockwell c and 47.0 rockwell c

**Accommodation Type And Quantity:**

2 slots

**Angle Between Accommodations In Deg:**

180.0

**Beveled Thread:**

Not included

**Bore Annular Internal Serration:**

Not included

**Setscrew Locking Notch:**

Not included

**Bore Edge Process:**

Chamfered

**Process End Location:**

End opposite drive end

**Material:**

Steel, ams 5643

**Material:**

Steel comp 630

**Surface Treatment:**

Passivate

**Surface Treatment:**

Passivated

**Fsc Application Data:**

Gyroscope, displacement

**Departure From Cited Designator:**

Nouf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T252-d