NSN 5365-00-646-7618

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-646-7618

Thread Pitch Diameters:			
+2.5404 to 2.5455 inches			
Thread Direction:			
Right-hand			
Casehardening Indicator:			
Not casehardened			
Chamfer Angle In Deg:			
45.0			
Chamfer Length:			
Between 0.052 inches and 0.072 inches			
Width:			
Between 0.250 inches and 0.265 inches			
Overall Length:			
Between 0.245 inches and 0.255 inches			
End Radius:			
1.289 inches			
Thread Size:			
2.578-20			
Bore Diameter:			
Between 2.188 inches and 2.219 inches			
Depth:			
0.215 inches			
Bore Shape:			
Straight			
Screw Thread Series Designator:			
Uns			
Drive Type:			
Keyway			
Material Hardness Rating:			
Between 35.0 rockwell c and 40.0 rockwell c			
Thread Location:			
Both ends			
Beveled Thread:			
Included			
Bore Annular Internal Serration:			
Not included			
Setscrew Locking Notch:			
Not included			
Bore Edge Process:			
Chamfered			
Process End Location:			
Both ends			

NSN 5365-00-646-7618

Externally Threaded Ring - Page 2 of 2



ΝЛ	ate	ria	
IVI	ale	па	I -

Steel, e-8740-6 alloy

Material:

Steel, e-8740-6 alloy

Surface Treatment:

Cadmium, qq-p-416, type 2

Surface Treatment:

Cadmium, qq-p-416, type 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d