NSN 5365-00-652-6296

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-652-6296 **Thread Class:** За **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Chamfer Angle In Deg:** 45.0 **Chamfer Length:** 0.062 inches **Overall Length:** 1.062 inches Diameter: 0.531 inches **Thread Size:** 4.500-12 **Bore Diameter:** 3.2500 inches Depth: 0.250 inches Bore Shape: Straight **Screw Thread Series Designator:** 12un **Drive Type:** Drilled face **Material Hardness Rating:** C29 to c34 **Thread Location:** End opposite drive end **Accommodation Type And Quantity:** Angle Between Accommodations In Deg: 90.0 **Radius From Geometric Axis To Accommodation:** 2.000 inches **Beveled Thread: Bore Annular Internal Serration:**

Included Not included **Setscrew Locking Notch:** Not included

NSN 5365-00-652-6296

Externally Threaded Ring - Page 2 of 2



| Bore Edge Process: |
|---|
| Chamfered |
| Process End Location: |
| End opposite drive end |
| Material: |
| Steel, federal standard 66, aisi/sae 1040 |
| Material: |
| Steel comp 1040 |
| Surface Treatment: |
| Phosphate |
| Surface Treatment: |
| Phosphate |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

T252-d