

View Online at <https://aerobasegroup.com/nsn/5365-00-658-3560>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Casehardening Indicator:**

Not casehardened

**Chamfer Angle In Deg:**

45.0

**Chamfer Length:**

0.070 inches

**Width:**

Between 0.120 inches and 0.140 inches

**Overall Length:**

Between 0.420 inches and 0.440 inches

**Thread Size:**

2-5/8 in. -12

**Bore Diameter:**

Between 2.250 inches and 2.270 inches

**Depth:**

Between 0.120 inches and 0.150 inches

**Bore Shape:**

Straight

**Screw Thread Series Designator:**

12n or 12un

**Drive Type:**

Slotted face

**Accommodation Type And Quantity:**

4 slots

**Angle Between Accommodations In Deg:**

90.0

**Beveled Thread:**

Not included

**Bore Annular Internal Serration:**

Not included

**Setscrew Locking Notch:**

Not included

**Bore Edge Process:**

Chamfered

**Process End Location:**

End opposite drive end

**Material:**

Aluminum alloy, qq-a-325, t6-canceled

**Material:**

Aluminum alloy 6061

**Surface Treatment:**

Anodize

**Surface Treatment:**

Anodized

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T252-d