NSN 5365-00-658-3560

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-658-3560 **Thread Class:** За **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened Chamfer Angle In Deg: 45.0 **Chamfer Length:** 0.070 inches Width: Between 0.120 inches and 0.140 inches **Overall Length:** Between 0.420 inches and 0.440 inches **Thread Size:** 2-5/8 in. -12 **Bore Diameter:** Between 2.250 inches and 2.270 inches Depth: Between 0.120 inches and 0.150 inches Bore Shape: Straight **Screw Thread Series Designator:** 12n or 12un **Drive Type:** Slotted face **Accommodation Type And Quantity:** Angle Between Accommodations In Deg: 90.0 **Beveled Thread:** Not included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Bore Edge Process:**

Chamfered **Process End Location:** End opposite drive end Material: Aluminum alloy, qq-a-325, t6-canceled

NSN 5365-00-658-3560

Externally Threaded Ring - Page 2 of 2



M	lat	Or	וכו	

Aluminum alloy 6061

Surface Treatment:

Anodize

Surface Treatment:

Anodized

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

T252-d