NSN 5365-00-662-9876

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-662-9876 **Thread Class:** 2a **Thread Direction:** Left-hand **Casehardening Indicator:** Not casehardened Chamfer Angle In Deg: 45.0 **Chamfer Length:** 0.063 inches Width: 0.200 inches **Overall Length:** 0.380 inches **Thread Size:** 2.625 in.-16 **Bore Diameter:** 2.160 inches Depth: 0.100 inches Bore Shape: Straight **Screw Thread Series Designator:** Un **Drive Type:** Slotted face **Material Hardness Rating:** Between 27.0 rockwell c and 32.0 rockwell c **Accommodation Type And Quantity:** 4 slots Angle Between Accommodations In Deg: **Radius From Geometric Axis To Accommodation:** 1.210 inches **Beveled Thread:** Not included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:**

Not included

Bore Edge Process:
Chamfered

NSN 5365-00-662-9876

Externally Threaded Ring - Page 2 of 2



Process End Location:

End opposite drive end

Material:

Steel, mil-s-18729, cond n

Material:

Steel comp 4130

Surface Treatment:

Cadmium

Surface Treatment:

Cadmium plated

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

T252-d