Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-664-0821

| Thread Class: | |
|---|---|
| За | |
| Thread Direction: | |
| Right-hand | |
| Casehardening Indicator: | |
| Not casehardened | |
| Width: | |
| 0.125 inches | |
| Overall Length: | |
| 0.469 inches | |
| Thread Size: | |
| 3-1/8 in12 | |
| Bore Diameter: | |
| 2.705 inches | |
| Depth: | |
| 0.063 inches | |
| Bore Shape: | |
| Straight | |
| Screw Thread Series Designator: | |
| 12n | |
| Drive Type: | |
| Slotted face | |
| Thread Location: | |
| End opposite drive end | |
| Accommodation Type And Quantity: | |
| 4 slots | |
| Angle Between Accommodations In Deg: | |
| 90.0 | |
| Beveled Thread: | |
| ncluded | |
| Bore Annular Internal Serration: | |
| Not included | |
| Setscrew Locking Notch: | |
| Not included | |
| Special Features: | |
| N/2.802 in. Diameter counterbore cut 0.104 in. Deep into id on end opposite drive end | d |
| Material: | |
| Bronze manganese, qq-b-728, class a, comp 1/2 hard | |
| Material: | |
| Copper alloy 675 | |
| Fsc Application Data: | |

Catapult, aircraft launching

NSN 5365-00-664-0821

Externally Threaded Ring - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d

