

View Online at <https://aerobasegroup.com/nsn/5365-00-664-2231>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Width:**

0.094 inches

**Overall Length:**

0.250 inches

**Thread Size:**

1.188-40

**Bore Diameter:**

0.906 inches

**Depth:**

0.063 inches

**Bore Shape:**

Straight

**Screw Thread Series Designator:**

Uns

**Drive Type:**

Slotted face

**Thread Location:**

Drive end

**Accommodation Type And Quantity:**

4 slots

**Angle Between Accommodations In Deg:**

90.0

**Beveled Thread:**

Included

**Bore Annular Internal Serration:**

Not included

**Setscrew Locking Notch:**

Not included

**Material:**

Brass, qq-b-626, comp 11

**Material:**

Copper alloy 260 or copper alloy 262 or copper alloy 268 or copper alloy 270 or copper alloy 272 or copper alloy 274 or copper alloy 280 or copper alloy 330 or copper alloy 331 or copper alloy 332 or copper alloy 335 or copper alloy 340 or copper alloy 342 or copper alloy 344 or copper alloy 345 or copper alloy 347 or copper alloy 348 or copper alloy 350 or copper alloy 353 or copper alloy 356 or copper alloy 360 or copper alloy 370 or copper alloy 462 or copper alloy 464 or copper alloy 465 or copper alloy 466 or copper alloy 467 or copper alloy 482 or copper alloy 485

**Fsc Application Data:**

Transmitter, oil pressure engine instrument, aircraft

**Shelf Life:**

N/a

**Unit Of Measure:**

**Demilitarization:**

No

**Fig:**

T252-d