Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-664-3043

| Thread Class: |
|--------------------------------------|
| 2a |
| Thread Direction: |
| Right-hand |
| Casehardening Indicator: |
| Not casehardened |
| Chamfer Angle In Deg: |
| 45.0 |
| Chamfer Length: |
| 0.060 inches |
| Width: |
| 0.125 inches |
| Overall Length: |
| 0.500 inches |
| Thread Size: |
| 1/4 in12 |
| Bore Diameter: |
| 0.753 inches |
| Depth: |
| 0.125 inches |
| Bore Shape: |
| Straight |
| Screw Thread Series Designator: |
| Unf |
| Drive Type: |
| Slotted face |
| Accommodation Type And Quantity: |
| 2 slots |
| Angle Between Accommodations In Deg: |
| 180.0 |
| Beveled Thread: |
| Not included |
| Bore Annular Internal Serration: |
| Not included |
| Setscrew Locking Notch: |
| Not included |
| Bore Edge Process: |
| Chamfered |
| Process End Location: |
| Both ends |
| Material: |
| Bronze |
| |

NSN 5365-00-664-3043

Externally Threaded Ring - Page 2 of 2

Material:

Copper alloy

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

T252-d

