## NSN 5365-00-664-4495

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-664-4495

Thread Class:
2a
Thread Direction:
Right-hand Casebardening Indicator:
Casehardening Indicator:  Not casehardened
Overall Length:
0.250 inches
Diameter:
0.096 inches
Thread Size:
7/8 in20
Bore Diameter:
0.250 inches
Depth:
0.063 inches
Bore Shape:
Straight
Screw Thread Series Designator:
Nef or unef
Drive Type:
Drilled face
Accommodation Type And Quantity:
2 holes
Angle Between Accommodations In Deg:
180.0
Radius From Geometric Axis To Accommodation:
0.2655 inches
Beveled Thread:
Not included
Bore Annular Internal Serration:
Not included
Setscrew Locking Notch:
Not included
Special Features:
0.500 in. Diameter by 0.0625 in. Deep counterbore under side of ring; 1/32 in. By 45 degree chamfer on both end of od
Material:
Brass, qq-b-626, alloy 360
Material:
Copper alloy 360
Fsc Application Data:

Hydraulic gear pump, turret traversing, tank

## NSN 5365-00-664-4495

Externally Threaded Ring - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

T252-d