## NSN 5365-00-664-4683

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-664-4683 **Thread Class:** 2a **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Chamfer Angle In Deg:** 45.0 **Chamfer Length:** 0.016 inches Width: 0.0312 inches **Overall Length:** 0.125 inches **Thread Size:** 13/16 in. -32 **Bore Diameter:** 0.625 inches Depth: 0.030 inches Bore Shape: Straight **Screw Thread Series Designator:** Uns **Drive Type:** Slotted face **Accommodation Type And Quantity:** Angle Between Accommodations In Deg: 180.0 **Beveled Thread:** Not included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Bore Edge Process:** Chamfered

**Process End Location:** End opposite drive end Material: Aluminum alloy, ww-t-785, t3-canceled

## NSN 5365-00-664-4683

Externally Threaded Ring - Page 2 of 2



M	lat	Or	וכו	

Aluminum alloy 2024

**Surface Treatment:** 

Anodize

**Surface Treatment:** 

Anodized

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

T252-d