## NSN 5365-00-664-9670

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-664-9670 **Thread Class:** 2a **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened Width: 0.188 inches **Overall Length:** 0.438 inches **Thread Size:** 3/4-16 **Bore Diameter:** 0.500 inches Depth: 0.125 inches **Bore Shape:** Straight **Screw Thread Series Designator:** Unf **Drive Type:** Slotted face **Thread Location:** Both ends **Accommodation Type And Quantity:** 2 slots Angle Between Accommodations In Deg: 180.0 **Beveled Thread:** Included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Special Features:** 4 (0.062 in. Dia) holes spaced 45 degrees apart, drilled through ring at drive end Material: Steel, ams 5640 Material: Steel comp 303 or steel comp 303se or steel comp 303 plus x

**Fsc Application Data:** 

Valve, anti-icing, jet engine, aircraft

## NSN 5365-00-664-9670

Externally Threaded Ring - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

T252-d