## NSN 5365-00-674-9468

Machine Thread Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5365-00-674-9468

Tread Direction:         Right-hand         Stor Uricht         Between 0.020 inches and 0.030 inches         Stot Width:         0.047 inches         Overall Length:         3.843 inches         Wenching Facility Shape:         Stotted         Between 2.661 inches and 2.662 inches         Width Across Flats:         Between 0.872 inches and 0.877 inches         Hole Inside Diameter:         0.860 inches         Thread Size:         0.875 inches         Material:         Copper alloy         Material:         Qapo-530 federal specification single material response         Thread Size:         Na         Material:         Copper alloy         Material Specification         Na         Material:         Na         Hole Measure:         Na         Sheed Netseuse:         Na         Sheed Netseuse:         Sheed Netseuse:         Between O.872 inchesing Netseuse         Between O.872 inchesing Netseuse         Between O.872 inchesing Netseuse         Na         Desperimentatin Response	
Slot Depti:         Between 0.020 inches and 0.030 inches         Slot Width:         0.047 inches         Out7 inches         Out7 inches         Out81 Length:         3.843 inches         Wrenching Facility Shape:         Slotted         Stored Thread Length:         Between 2.661 inches and 2.662 inches         Width Across Flats:         Between 0.872 inches and 0.877 inches         Hole Inside Diameter:         0.580 inches         Thready Qty Per Inch (tpi):         18         Capper alloy         Material         Quero-S30 federal specification single material response         Thread Stere:         Inve         Inve         Inter Consensensensensensensensensensensensensen	Thread Direction:
Between 0.020 inches and 0.030 inches         Stot Width:         0.047 inches         Overall Length:         3.843 inches         Wenching Facility Shape:         Stotted         Pereer Thread Length:         Between 0.872 inches and 2.662 inches         Width Across Flats:         Between 0.872 inches and 0.877 inches         Hole Inside Diameter:         0.580 inches         Thread Y QP Per Inch (tpi):         18         Material:         0.875 inches         Material:         0.975 inches         Material:         18         Material: <th>Right-hand</th>	Right-hand
Slot Width:0.047 inches0.verall Length:3.843 inchesWenching Facility Shape:SlottedStorew Thread Length:Between 2.661 inches and 2.662 inchesWidth Across Flats:Between 0.872 inches and 0.877 inchesHole Inside Diameter:0.580 inchesThread Size:0.875 inchesMaterial:Copper alloyMaterial Specification single material responseThread Steise Designator:UnsShell Life:N/aDing Diameter:0.875 inchesGaries Designator:Image: Designator:Ima	Slot Depth:
0.047 inchesOverall Length:3.843 inchesWrenching Facility Shape:SlottedSorter Thread Length:Between 2.661 inches and 2.662 inchesWith Across Flats:Between 0.872 inches and 0.877 inchesHole Inside Diameter:0.580 inchesThready Qty Per Inch (tpi):18Thread Size:0.875 inchesMaterial:Copper alloyMaterial Specification single material responseThread Series Designator:UnsSheft Life:NaNaFine:NaFine:NaFine:NaFine:NaFine:NaFine:NaFine:NaFine:NaFine:NaFine:NaFine:NaFine:NaFine:NaFine:NaFine: </th <th>Between 0.020 inches and 0.030 inches</th>	Between 0.020 inches and 0.030 inches
Overall Length:3.843 inchesWrenching Facility Shape:SlottedSorter Thread Length:Between 2.661 inches and 2.662 inchesWidth Across Flats:Between 0.872 inches and 0.877 inchesHole Inside Diameter:0.580 inchesThready Qty Per Inch (tpi):18Breven 10.872 inchesMaterial:Copper alloyMaterial Specification single material responseThread Streis Designator:UnsShelf Life:NaDird Measure:NaFing:NaFing:Na </th <th>Slot Width:</th>	Slot Width:
3.843 inches         Wrenching Facility Shape:         Slotted         Screw Thread Length:         Between 2.661 inches and 2.662 inches         Width Across Flats:         Between 0.872 inches and 0.877 inches         Hole Inside Diameter:         0.580 inches         Thready Qty Per Inch (tpi):         18         Thread Size:         0.875 inches         Material:         Copper alloy         Material Specification single material response         Thread Series Designator:         Uns         Sheff Life:         N/a         Dirt of Measure:         Image:         No         Fig:	0.047 inches
Wrenching Facility Shape:SlottedScrew Thread Length:Between 2.661 inches and 2.662 inchesWidth Across Flats:Between 0.872 inches and 0.877 inchesHole Inside Diameter:0.580 inchesThready Qty Per Inch (tpi):18Thread Size:0.875 inchesMaterial:Copper alloyMaterial Specification single material responseThread Size:0.420-530 federal specification single material responseThread Size:ViaMaterial:Copper alloy:Differial:Material:Intread Size:Intread Size:Intersec:Inters	Overall Length:
Slotted Srow Thread Length: Between 2.661 inches and 2.662 inches Width Across Flats: Between 0.872 inches and 0.877 inches Hole Inside Diameter: 0.580 inches Thready Qty Per Inch (tpi): 18 Thread Size: 0.875 inches Material: Coper alloy Material: Coper alloy Material Specification: Cq-c-530 federal specification single material response Thread Series Designator: Uns Shelf Life: N/a Dint of Measure: - Dintilatrization: No Fig:	3.843 inches
Screw Thread Length:Between 2.661 inches and 2.662 inchesWidth Across Flats:Between 0.872 inches and 0.877 inchesHole Inside Diameter:0.580 inchesThready Qty Per Inch (tpi):18Thread Size:0.875 inchesMaterial:Copper alloyMaterial Specification:Qr-c-530 federal specification single material responseThread Series Designator:UnsShelf Life:N/aDir of Measure:Pomilitarization:NoFig:	Wrenching Facility Shape:
Between 2.661 inches and 2.662 inches         Width Across Flats:         Between 0.872 inches and 0.877 inches         Hole Inside Diameter:         0.580 inches         Thready Qty Per Inch (tpi):         18         Thread Size:         0.875 inches         Material:         Copper alloy         Material Specification         Qq-c-530 federal specification single material response         Thread Series Designator:         Uns         Shelf Life:         Na         Info Measure:         -         Info Measure:         No         Fig:	Slotted
Width Across Flats:Between 0.872 inches and 0.877 inchesHole Inside Diameter:0.580 inchesThready Qty Per Inch (tpi):18Thread Size:0.875 inchesMaterial:Copper alloyMaterial Specification:Qq-c-530 federal specification single material responseThread Series Designator:UnsShelf Life:N/aInti Of Measure:Pinci Minization:Fig:	Screw Thread Length:
Between 0.872 inches and 0.877 inches         Hole Inside Diameter:         0.580 inches         Thready Qty Per Inch (tpi):         18         Thread Size:         0.875 inches         Material:         Copper alloy         Material Specification:         Qq-c-530 federal specification single material response         Thread Series Designator:         Uns         Shelf Life:         N/a         Unit Of Measure:            Demiliarization:         No         Fig:	Between 2.661 inches and 2.662 inches
Hole Inside Diameter:         0.580 inches         Thready Qty Per Inch (tpi):         18         Thread Size:         0.875 inches         Material:         Copper alloy         Material Specification:         Qq-c-530 federal specification single material response         Thread Series Designator:         Uns         Shelf Life:         N/a         Unit Of Measure:         -         Demilitarization:         No         Fig:	Width Across Flats:
0.580 inches  Thready Qty Per Inch (tpi):  18  Thread Size:  0.875 inches  Material:  Copper alloy  Material Specification:  Qq-c-530 federal specification single material response  Thread Series Designator:  Uns  Shelf Life:  N/a  Unit Of Measure:   Demiltarization:  No  Fig:	Between 0.872 inches and 0.877 inches
Thready Qty Per Inch (tpi):1818Fhread Size:0.875 inchesMaterial:Copper alloyMaterial Specification:Qq-c-530 federal specification single material responseThread Series Designator:UnsShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Hole Inside Diameter:
18 Thread Size: 0.875 inches Material: Copper alloy Material Specification: Qq-c-530 federal specification single material response Thread Series Designator: Uns Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	0.580 inches
Thread Size:0.875 inchesMaterial:Copper alloyMaterial Specification:Qq-c-530 federal specification single material responseThread Series Designator:UnsShelf Life:N/aUnt Of Measure:Demilitarization:NoFig:	Thready Qty Per Inch (tpi):
0.875 inches Material: Copper alloy Material Specification: Qq-c-530 federal specification single material response Chread Series Designator: Uns Shelf Life: N/a Dit Of Measure:  Pemilitarization: No Fig:	18
Material:Copper alloyMaterial Specification:Qq-c-530 federal specification single material responseThread Series Designator:UnsShelf Life:N/aUni Of Measure:Demilitarization:NoFig:	Thread Size:
Copper alloy Material Specification: Qq-c-530 federal specification single material response Thread Series Designator: Uns Shelf Life: N/a Unit Of Measure: Fig:	0.875 inches
Material Specification:Qq-c-530 federal specification single material responseThread Series Designator:UnsShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Material:
Qq-c-530 federal specification single material response   Thread Series Designator:   Uns   Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No   Fig:	Copper alloy
Thread Series Designator:   Uns   Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No   Fig:	Material Specification:
Uns Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Qq-c-530 federal specification single material response
Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No   Fiig:	Thread Series Designator:
N/a Unit Of Measure:  Demilitarization: No Fiig:	Uns
Unit Of Measure:  Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A540s0	Fiig:
	A540s0