

View Online at <https://aerobasegroup.com/nsn/5365-00-678-1754>

Thread Class:

3

Thread Direction:

Right-hand

Casehardening Indicator:

Not casehardened

Width:

0.260 inches

Overall Length:

Between 0.655 inches and 0.665 inches

Thread Size:

3-1/16 in. - 16

Bore Diameter:

Between 2.460 inches and 2.470 inches

Depth:

Between 0.235 inches and 0.245 inches

Bore Shape:

Straight

Screw Thread Series Designator:

Ns

Drive Type:

Slotted face

Thread Location:

End opposite drive end

Accommodation Type And Quantity:

15 slots

Angle Between Accommodations In Deg:

24.0

Beveled Thread:

Included

Bore Annular Internal Serration:

Not included

Setscrew Locking Notch:

Not included

Special Features:

2.780 in. Od of drive end and 2.760 in. Diameter by 0.260 in. Deep counterbore at end opposite to drive end

Material:

Steel, aisi mt1015 or steel, qq-s-698 or iron, qq-i-666, grade 1 or iron, qq-i-666, grade 2

Material:

Steel comp mt1015 or steel comp 1008 or steel comp 1009 or steel comp 1015 or steel comp 1018 or steel comp 1020 or steel or iron cast uns f22400 or iron cast uns f22200

Fsc Application Data:

Differential, utility truck

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d