

View Online at <https://aerobasegroup.com/nsn/5365-00-678-1754>

**Thread Class:**

3

**Thread Direction:**

Right-hand

**Casehardening Indicator:**

Not casehardened

**Width:**

0.260 inches

**Overall Length:**

Between 0.655 inches and 0.665 inches

**Thread Size:**

3-1/16 in. - 16

**Bore Diameter:**

Between 2.460 inches and 2.470 inches

**Depth:**

Between 0.235 inches and 0.245 inches

**Bore Shape:**

Straight

**Screw Thread Series Designator:**

Ns

**Drive Type:**

Slotted face

**Thread Location:**

End opposite drive end

**Accommodation Type And Quantity:**

15 slots

**Angle Between Accommodations In Deg:**

24.0

**Beveled Thread:**

Included

**Bore Annular Internal Serration:**

Not included

**Setscrew Locking Notch:**

Not included

**Special Features:**

2.780 in. Od of drive end and 2.760 in. Diameter by 0.260 in. Deep counterbore at end opposite to drive end

**Material:**

Steel, aisi mt1015 or steel, qq-s-698 or iron, qq-i-666, grade 1 or iron, qq-i-666, grade 2

**Material:**

Steel comp mt1015 or steel comp 1008 or steel comp 1009 or steel comp 1015 or steel comp 1018 or steel comp 1020 or steel or iron cast uns f22400 or iron cast uns f22200

**Fsc Application Data:**

Differential, utility truck

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T252-d