

View Online at <https://aerobasegroup.com/nsn/5365-00-678-1755>

**Thread Class:**

3a

**Casehardening Indicator:**

Not casehardened

**Width:**

0.260 inches

**Overall Length:**

Between 0.715 inches and 0.720 inches

**Thread Size:**

3.250-16

**Bore Diameter:**

2.640 inches

**Depth:**

0.250 inches

**Bore Shape:**

Straight

**Screw Thread Series Designator:**

Un

**Drive Type:**

Slotted face

**Thread Location:**

Both ends

**Accommodation Type And Quantity:**

15 slots

**Angle Between Accommodations In Deg:**

24.0

**Beveled Thread:**

Included

**Bore Annular Internal Serration:**

Not included

**Setscrew Locking Notch:**

Not included

**Special Features:**

63 microinch finish on bearing surface; id counterbored, end opposite to drive end, 2.960 in. Diameter by 0.3125 in. Applies

**Material:**

Steel, aisi mt1015 or steel, qq-s-698 or iron, qq-i-666, grade 1 or iron, qq-i-666, grade 2

**Material:**

Steel comp mt1015 or steel comp 1008 or steel comp 1009 or steel comp 1015 or steel comp 1018 or steel comp 1020 or steel or iron cast uns f22400 or iron cast uns f22200

**Fsc Application Data:**

Differential, truck

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T252-d