

View Online at <https://aerobasegroup.com/nsn/5365-00-678-1755>

Thread Class:

3a

Casehardening Indicator:

Not casehardened

Width:

0.260 inches

Overall Length:

Between 0.715 inches and 0.720 inches

Thread Size:

3.250-16

Bore Diameter:

2.640 inches

Depth:

0.250 inches

Bore Shape:

Straight

Screw Thread Series Designator:

Un

Drive Type:

Slotted face

Thread Location:

Both ends

Accommodation Type And Quantity:

15 slots

Angle Between Accommodations In Deg:

24.0

Beveled Thread:

Included

Bore Annular Internal Serration:

Not included

Setscrew Locking Notch:

Not included

Special Features:

63 microinch finish on bearing surface; id counterbored, end opposite to drive end, 2.960 in. Diameter by 0.3125 in. Applies

Material:

Steel, aisi mt1015 or steel, qq-s-698 or iron, qq-i-666, grade 1 or iron, qq-i-666, grade 2

Material:

Steel comp mt1015 or steel comp 1008 or steel comp 1009 or steel comp 1015 or steel comp 1018 or steel comp 1020 or steel or iron cast uns f22400 or iron cast uns f22200

Fsc Application Data:

Differential, truck

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T252-d