

View Online at <https://aerobasegroup.com/nsn/5365-00-680-3690>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Casehardening Indicator:**

Not casehardened

**Width:**

0.266 inches

**Overall Length:**

0.938 inches

**Thread Size:**

3-5/16 in. -16

**Bore Diameter:**

Between 2.374 inches and 2.376 inches

**Depth:**

0.375 inches

**Bore Shape:**

Straight

**Screw Thread Series Designator:**

Un

**Drive Type:**

Slotted face

**Accommodation Type And Quantity:**

12 slots

**Angle Between Accommodations In Deg:**

30.0

**Radius From Geometric Axis To Accommodation:**

2.594 inches

**Beveled Thread:**

Not included

**Bore Annular Internal Serration:**

Not included

**Setscrew Locking Notch:**

Not included

**Material:**

Copper alloy, qq-c-390

**Material:**

Copper alloy 820 or copper alloy 824 or copper alloy 825 or copper alloy 826 or copper alloy 827 or copper alloy 828 or copper alloy 836 or copper alloy 838 or copper alloy 842 or copper alloy 844 or copper alloy 848 or copper alloy 852 or copper alloy 854 or copper alloy 855 or copper alloy 857 or copper alloy 861 or copper alloy 862 or copper alloy 863 or copper alloy 864 or copper alloy 865 or copper alloy 868 or copper alloy 872 or copper alloy 874 or copper alloy 903 or copper alloy 905 or copper alloy 907 or copper alloy 910 or copper alloy 913 or copper alloy 915-canceled or copper alloy 916 or copper alloy 922 or copper alloy 923 or copper alloy 925 or copper alloy 927 or copper alloy 932 or copper alloy 934 or copper alloy 935 or copper alloy 937 or copper alloy 938 or copper alloy 939 or copper alloy 940 or copper alloy 941 or copper alloy 943 or copper alloy 947 or copper alloy 948 or copper alloy 952 or copper alloy 953 or copper alloy 954 or copper alloy 955 or copper alloy 957 or copper alloy 958 or copper alloy 962 or copper alloy 964

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T252-d