NSN 5365-00-680-8877

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-680-8877 **Thread Class:** 2a **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Overall Length:** 0.313 inches Diameter: 0.156 inches **Thread Size:** 1-1/8 in. -12 **Bore Diameter:** 0.344 inches Depth: 0.125 inches **Bore Shape:** Straight **Screw Thread Series Designator:** Unf or nf **Drive Type:** Drilled face **Accommodation Type And Quantity:** 2 holes Angle Between Accommodations In Deg: 180.0 **Radius From Geometric Axis To Accommodation:** 0.343 inches **Beveled Thread:** Not included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Special Features:** End opposite drive end has a raised face 5/8 in. Diameter by 1/16 in. H Material: Steel, mil-s-890, class an Material:

Fsc Application Data: Steam turbine

Steel

NSN 5365-00-680-8877

Externally Threaded Ring - Page 2 of 2



_				-		
C	h	0	Iŧ.		ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d