Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-685-1162

	hread Class:
3	a
Т	hread Direction:
F	light-hand
C	Casehardening Indicator:
Ν	lot casehardened
V	Vidth:
С	.250 inches
C	Overall Length:
1	.500 inches
E	nd Radius:
С	.031 inches
Т	hread Size:
2	-9/16 in20
E	Bore Diameter:
2	.242 inches
C	Depth:
С	.188 inches
E	Bore Shape:
S	Straight
S	crew Thread Series Designator:
Ν	ls
C	Prive Type:
S	Slotted face
A	accommodation Type And Quantity:
2	slots
A	ngle Between Accommodations In Deg:
1	80.0
E	Beveled Thread:
٩	lot included
E	Bore Annular Internal Serration:
Ν	lot included
S	Setscrew Locking Notch:
٩	lot included
E	Bore Edge Process:
F	Rounded
F	Process End Location:
E	Both ends
N	laterial:
C	Copper alloy, sae 40
	laterial:

NSN 5365-00-685-1162

Externally Threaded Ring - Page 2 of 2



Fsc Application Data:

Jack, hydraulic, tripod, aircraft

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

T252-d