NSN 5365-00-685-5773

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-685-5773 **Thread Class:** 2a **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened Width: 0.031 inches **Overall Length:** Between 0.070 inches and 0.080 inches **Thread Size:** 1-17/32 in. -32 **Bore Diameter:** 1.400 inches Depth: 0.030 inches **Bore Shape:** Straight **Screw Thread Series Designator:** Uns **Drive Type:** Slotted face **Accommodation Type And Quantity:** Angle Between Accommodations In Deg: 180.0 **Beveled Thread:** Not included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included Material: Aluminum alloy, 2024 or 6061, temper t3 through t6, spec ww-t-700/3, ww-t-700/6, qq-a-200/3, qq-a-200/8, qq-a-225/6, qq-a-225/8, qq-a-250/4 or qq-a-250/11 Material: Aluminum alloy, 2024 or 6061, temper t3 through t6, spec ww-t-700/3, ww-t-700/6, qq-a-200/3, qq-a-200/8, qq-a-225/6, qq-a-225/8, qq-a-250/4 or qq-a-250/11 **Surface Treatment:** Anodize **Surface Treatment:**

N/a

Anodized black Shelf Life:

NSN 5365-00-685-5773

Externally Threaded Ring - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

T252-d