

View Online at <https://aerobasegroup.com/nsn/5365-00-690-2339>

Thread Class:

3a

Thread Direction:

Right-hand

Casehardening Indicator:

Not casehardened

Width:

Between 0.110 inches and 0.130 inches

Overall Length:

Between 0.710 inches and 0.730 inches

End Radius:

0.200 inches

Thread Size:

0.938-20

Bore Diameter:

Between 0.385 inches and 0.395 inches

Depth:

Between 0.100 inches and 0.120 inches

Bore Shape:

Straight

Screw Thread Series Designator:

Unef

Drive Type:

Slotted face

Material Hardness Rating:

Between 28.0 rockwell c and 36.0 rockwell c

Thread Location:

Both ends

Accommodation Type And Quantity:

2 slots

Angle Between Accommodations In Deg:

180.0

Beveled Thread:

Not included

Bore Annular Internal Serration:

Not included

Setscrew Locking Notch:

Not included

Bore Edge Process:

Rounded

Process End Location:

Both ends

Material:

Steel, b50ta305b, 99207

Material:

Steel, b50ta305b, 99207

Surface Treatment:

Black oxide, ams 2485

Surface Treatment:

Black oxide, ams 2485

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T252-d