NSN 5365-00-695-7267

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-695-7267 **Thread Class:** За **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened Width: 0.760 inches **Overall Length:** 0.880 inches **Thread Size:** 5-1/2 (5.500) in. - 12 **Bore Diameter:** 4.120 inches Depth: 0.310 inches Bore Shape: Straight **Screw Thread Series Designator:** Un or n **Drive Type:** Slotted face **Thread Location:** Both ends **Accommodation Type And Quantity:** 4 slots Angle Between Accommodations In Deg: 90.0 **Beveled Thread:** Included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Special Features:** 0.440 in w, 4.620 in. Diameter counterbore drive end; 0.250 in. W, 4.620 in. Diameter counterbore opposite drive end Material: Steel, aisi mt1015 Material:

Fsc Application Data: Transmission, truck, tractor

Steel comp mt1015

NSN 5365-00-695-7267

Externally Threaded Ring - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d