Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-721-5229

View Online at https://aerobasegroup.com/nsn/5365-00-721-5229	
Thread Class:	
3a	
Thread Direction:	
Right-hand	
Casehardening Indicator:	
Not casehardened	
Overall Length:	
0.420 inches	
Diameter:	
0.070 inches	
End Radius:	
0.030 inches	
Thread Size:	
0.760 in32	
Bore Diameter:	
0.265 inches	
Depth:	
0.100 inches	
Bore Shape:	
Straight	
Screw Thread Series Designator:	
Un	
Drive Type:	
Drilled face	
Thread Location:	
Both ends	
Accommodation Type And Quantity:	
3 holes	
Angle Between Accommodations In Deg:	
120.0	
Radius From Geometric Axis To Accommodation:	
0.250 inches	
Beveled Thread:	
Included	
Bore Annular Internal Serration:	
Not included	
Setscrew Locking Notch:	
Not included	
Bore Edge Process:	
Rounded	
Process End Location:	
Both ends	

## NSN 5365-00-721-5229

Externally Threaded Ring - Page 2 of 2



Special Features:

Counter bored to 0.281 in. Diameter by 0.330 in. Lg

Material:

Steel, qq-s-764, comp 303, cond a-canceled

Material:

Steel comp 303

Surface Treatment:

Passivate

Surface Treatment:

Passivated

Fsc Application Data:

Cylinder assembly, emergency oxygen, aircraft

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

No

Fiig:

T252-d