## NSN 5365-00-721-5321

**Fsc Application Data:** 

Gyro component, autopilot system

Externally Threaded Ring - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5365-00-721-5321



**Thread Class:** За **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened Width: 0.080 inches **Overall Length:** 0.250 inches **Thread Size:** 9/16 in. -40 **Bore Diameter:** 0.453 inches Depth: Between 0.040 inches and 0.055 inches **Bore Shape:** Straight **Screw Thread Series Designator:** Uns **Drive Type:** Slotted face **Accommodation Type And Quantity:** 2 slots Angle Between Accommodations In Deg: 180.0 **Beveled Thread:** Not included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included Material: Steel, qq-s-634-canceled Material: Steel comp 1010 or steel comp 1015 or steel comp 1016 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1022 or steel comp 1025 or steel comp 1026 or steel comp 1035 or steel comp 1040 or steel comp 1042 or steel comp 1045 or steel comp 1046 or steel comp 1548 or steel comp 1049 or steel comp 1050 **Surface Treatment:** Oxide **Surface Treatment:** Black oxide

## NSN 5365-00-721-5321

Externally Threaded Ring - Page 2 of 2



	Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

T252-d