NSN 5365-00-723-7401

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-723-7401 **Thread Class:** За **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Chamfer Angle In Deg:** 45.0 **Chamfer Length:** 0.060 inches **Overall Length:** 0.884 inches Diameter: 6.000 inches **Taper Minor Diameter:** Between 5.372 inches and 5.377 inches **Taper Major Diameter:** Between 5.880 inches and 5.885 inches **Thread Size:** 6 in. -12 **Bore Diameter:** Between 5.372 inches and 5.377 inches **Bore Shape:** Straight **Screw Thread Series Designator:** 12 un or 12 n **Drive Type:** Lug face **Material Hardness Rating:** C39 to c43 **Accommodation Type And Quantity:** Angle Between Accommodations In Deg: 45.0 **Beveled Thread:** Not included **Taper Major Diameter Location:** Opposite drive end **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:**

Not included

NSN 5365-00-723-7401Externally Threaded Ring - Page 2 of 2



Bore Edge Process:
Chamfered
Process End Location:
End opposite drive end
Height:
0.198 inches
Material:
Steel, mil-t-6736, type 1, cond n
Material:
Steel comp 4130
Surface Treatment:
Cadmium
Surface Treatment:
Cadmium plated
Fsc Application Data:
Rotor assembly, aircraft
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
T252-d