NSN 5365-00-723-8924

Demilitarization:

No

Machine Thread Bushing - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-723-8924

view Offiline at https://aerobasegroup.com/nsh/osos-oo-725-os24	
Thread Pitch Diameters:	
+0.7445/+0.7490 inches	
Thread Direction:	
Right-hand	
Countersink Angle In Deg:	
60.0	
Overall Length:	
2.680 inches	
Thickness:	
0.240 inches	
Wrenching Facility Shape:	
Hexagon	
Countersink Depth:	
0.030 inches	
Screw Thread Length:	
0.830 inches	
Width Across Flats:	
0.710 inches	
Countersink Location:	
Threaded end and wrenching end	
Hole Inside Diameter:	
0.375 inches	
Features Provided:	
Countersunk	
Thread Size:	
20.0 millimeters	
Thread Pitch In Millimeters:	
1.50	
Special Features:	
1 in. Diameter extended washer under head 0.080 in. Thk, 0.680 in. Diameter by 0.120 w thd relief under washer, 0.699 in. Diameter by	
1.410 in. Lg of unthreaded portion from thd to male end, male end caseherdened 1.410 in. Lg, rock a scale 79 to 84 hardness, 32	
microinches rms on unthreaded male end	
Material:	
Steel	
Surface Treatment:	
Phosphate	
Thread Series Designator:	
International metric fine thread	
Shelf Life:	
N/a	
Unit Of Measure:	

NSN 5365-00-723-8924

Machine Thread Bushing - Page 2 of 2



Fiig:

A540s0