Machine Thread Bushing - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-723-8924

Thread Pitch Diameters:

+0.7445/+0.7490 inches

Thread Direction:

Right-hand

Countersink Angle In Deg:

60.0

Overall Length:

2.680 inches

Thickness:

0.240 inches

Wrenching Facility Shape:

Hexagon

Countersink Depth:

0.030 inches

Screw Thread Length:

0.830 inches

Width Across Flats:

0.710 inches

Countersink Location:

Threaded end and wrenching end

Hole Inside Diameter:

0.375 inches

Features Provided:

Countersunk

Thread Size:

20.0 millimeters

Thread Pitch In Millimeters:

1.50

Special Features:

1 in. Diameter extended washer under head 0.080 in. Thk, 0.680 in. Diameter by 0.120 w thd relief under washer, 0.699 in. Diameter by 1.410 in. Lg of unthreaded portion from thd to male end, male end caseherdened 1.410 in. Lg, rock a scale 79 to 84 hardness, 32 microinches rms on unthreaded male end

Material:

Steel

Surface Treatment:

Phosphate

Thread Series Designator:

International metric fine thread

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5365-00-723-8924

Machine Thread Bushing - Page 2 of 2

Fiig: A540s0

