## NSN 5365-00-724-0482

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-724-0482 **Thread Class:** 2a **Thread Pitch Diameters:** +0.8821 to 0.8859 inches **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Chamfer Angle In Deg:** 45.0 **Chamfer Length:** 0.031 inches Width: 0.625 inches **Overall Length:** 0.160 inches **Thread Size:** 29/32 in. -32 **Bore Diameter:** 0.703 inches Depth: 0.625 inches **Bore Shape:** Straight **Screw Thread Series Designator:** Uns **Drive Type:** Slotted face Between 39.0 rockwell c and 47.0 rockwell c Angle Between Accommodations In Deg:

**Material Hardness Rating: Accommodation Type And Quantity:** 360.0 **Beveled Thread:** Not included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Bore Edge Process:** Chamfered

## NSN 5365-00-724-0482

Externally Threaded Ring - Page 2 of 2



_				_							
0	-	~~	00	Er	~~		100	٠ŧi	_	n	
Г1	··	υC	33		ıu	ᆫ	Juc	ııı	u	. 1	

End opposite drive end

Material:

Steel, ams 5643

Material:

Steel comp 630

**Surface Treatment:** 

Cadmium

**Surface Treatment:** 

Cadmium plated

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

**Demilitarization:** 

No

Fiig:

T252-d