## NSN 5365-00-730-7494

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-730-7494 **Thread Class:** 2a **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened Diameter: Between 0.187 inches and 0.197 inches **Thread Size:** 3-3/8 in. -16 **Bore Diameter:** Between 2.750 inches and 2.760 inches Depth: 0.250 inches **Bore Shape:** Straight **Screw Thread Series Designator:** 16 n **Drive Type:** Drilled face **Accommodation Type And Quantity:** 4 holes Angle Between Accommodations In Deg: **Radius From Geometric Axis To Accommodation:** 1.500 inches **Beveled Thread:** Not included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Special Features:** 0.093 in. W by 3.280 in. Diameter thd relief and 3.500 in. Od by 0.089 in. Wide lip next to thd relief Material: Steel, carbon Material: Steel **Surface Treatment:** Phosphate **Surface Treatment:** 

Phosphate

## NSN 5365-00-730-7494

Externally Threaded Ring - Page 2 of 2



	Fsc	App	lication	Data:
--	-----	-----	----------	-------

Rifle, 106-mm, m40

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

T252-d