Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-752-1779

Thread	Direction:

**Right-hand** 

#### **Casehardening Indicator:**

Not casehardened

Width:

0.406 inches

#### **Overall Length:**

4.270 inches

#### Thread Size:

4.422-12

Bore Diameter:

3.000 inches

#### Depth:

0.375 inches

#### **End Application:**

Truck, forklift, ded 6000 lb variable; helicopter, carrier based asw, sh-60f; truck, cargo, dropside 2 1/2-ton 6x6 w/e; helicopter, search and rescue, hh-60h; helcopter, uscg search and rescue, hh-60j; shipboard material handling equipment (mhe); helicopter, advance attack, ah-1w; truck, fl (m4k); helciopter, mh-53e

#### Bore Shape:

Straight

#### **Screw Thread Series Designator:**

Uns

Drive Type:

Slotted face

#### **Material Hardness Rating:**

Between 57.0 rockwell c and 63.0 rockwell c

#### Accommodation Type And Quantity:

17 slots

#### Angle Between Accommodations In Deg:

90.0

#### **Beveled Thread:**

Not included

## Bore Annular Internal Serration:

Not included

## Setscrew Locking Notch:

Not included

## Material:

Iron, cast

# Material:

Iron cast

# Shelf Life:

N/a

# Unit Of Measure:

# NSN 5365-00-752-1779

Externally Threaded Ring - Page 2 of 2

Demilitarization:

No

Fiig:

T252-d

