## NSN 5365-00-752-4788



Externally Threaded Ring - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5365-00-752-4788 **Thread Class:** 2a **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Chamfer Angle In Deg:** 45.0 **Chamfer Length:** 0.063 inches Width: 0.188 inches **Overall Length:** 0.375 inches **Thread Size:** 3 in. - 12 **Bore Diameter:** 2.375 inches Depth: 0.188 inches **Bore Shape:** Straight **Screw Thread Series Designator: Drive Type:** Slotted face **Accommodation Type And Quantity:** Angle Between Accommodations In Deg: 90.0 **Beveled Thread:** Not included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Bore Edge Process:** Chamfered **Process End Location:** Both ends Material: Steel, qq-s-634, comp 1020-canceled and steel, qq-s-634, comp 1025-canceled

## NSN 5365-00-752-4788

Externally Threaded Ring - Page 2 of 2



Material	
waterial	

Steel comp 1020 and steel comp 1025

## **Material Specification:**

Qq-s-634, comp 1020-canceled federal specification 1st material response and qq-s-634, comp 1025-canceled federal specification 2nd material response

## **Surface Treatment:**

Zinc or cadmium and dichromate

**Surface Treatment:** 

Zinc or cadmium dichromate

**Fsc Application Data:** 

Mount, howitzer, 155-mm, m80

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

T252-d