NSN 5365-00-752-7186

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-752-7186

Thread Pitch Diameters:
+10.1320 to 10.1420 inches
Thread Direction:
Right-hand
Casehardening Indicator:
Not casehardened
Chamfer Angle In Deg:
45.0
Chamfer Length:
0.031 inches
Width:
0.500 inches
Overall Length:
1.483 inches
Thread Size:
10.187 in, dia - 0.1p - 6 degrees - nr
Bore Diameter:
9.281 inches
Depth:
0.3125 inches
Bore Shape:
Straight
Screw Thread Series Designator:
Nonstandard
Drive Type:
Externally slotted
Material Hardness Rating:
C30 to c34
Thread Location:
Both ends
Accommodation Type And Quantity:
6 slots
Angle Between Accommodations In Deg:
60.0
Beveled Thread:
Included
Bore Annular Internal Serration:
Not included
Setscrew Locking Notch:
Not included
Bore Edge Process:
Chamfered

NSN 5365-00-752-7186

Fiig: T252-d

Externally Threaded Ring - Page 2 of 2



Process End Location:
End opposite drive end
Special Features:
Counterbored raised boss on end opposite to drive end, grooved on drive face end and ends chamfered, see card 2 of 2 for sketch
Material:
Steel, mil-s-13048-canceled
Material:
Steel
Fsc Application Data:
Cradle assembly, cylinder assembly, concentric recoil, mount combination, gun, 76mm, m32
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No